



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Wednesday, May 19, 2021** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=81870&Standard=061&>

## NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

**NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).**

### Dorot Management Control Valves Ltd.

<http://www.dorot.com>

Kibbutz Dorot

Mobile Post Hof Ashkelon 79175

Israel

972 8 680 8576

[Visit this company's website \(http://www.dorot.com\)](http://www.dorot.com)

**Facility :** Kibbutz Dorot, M.P. Hof Ashkelon, Israel

### Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
<b>Valves</b>			
DAV-MH Air Release and Vacuum Break Valve[1] [G]	2" - 10"	CLD 23	MLTPL
DAV-MH-SA Air Release and Vacuum Break Valve[1] [G]	2" - 10"	CLD 23	MLTPL

DAV-MS Air Release and Vacuum Break Valve[1] [G]	2" - 12"	CLD 23	MLTPL
DAV-MS-SA Air Release and Vacuum Break Valve[1] [G]	2" - 12"	CLD 23	MLTPL
DAV-P-(X)-(Y)-(Z)-PN16[2]	1/2" - 2"	CLD 23	MLTPL
Series 300[3] [G]	1.5" - 40"	CLD 23	MLTPL

[1] Products may have a K or KA suffix.

[2] DAV - Dorot Control Valve

P - Plastic Body & Cover

X - Size

05 - 1/2" / 12 mm

75 - 3/4" / 20 mm

1 - 1" / 25mm

2 - 2" / 50 mm

Y - Function

A - Automatic

K - Kinetic

KA - Kinetic Automatic Combination

Z - Connection Standard

BSP - British Standard Pipe

NPT - National Pipe Thread

PN16 - Pressure Rating (230 psi)

Note: 2" / 50 mm available with K or KA functions only

[3] Certified for the following 300 Series Valves:

Series 300 hydraulic valves (3x-yy models)

Float-actuated valves (3x-yy-FLzz models)

Electronically-controlled, solenoid-valve actuated valves( 3x-yy-EC models)

Electrically controlled and electric-float controlled valves (3x-yy-EL models)

Altitude control valves (3x-yy-AL-CXAL models)

Rate-of-flow limiting valves (3x-yy-FR models)

Pressure reducing valves (3x-yy-PR models)

Pressure sustaining & sustaining\relief valves (3x-yy-PS models)

Quick pressure-relief valves (3x-yy-QR models)

Booster pump control valves (3x-yy-BC models)

3x: includes basic valve models 30, 31 and 32. "yy" - designates the valve size: 1.5" - 40"

3x -FLyy: Includes models 3x-FL and 3x-FLDI (3x-FL is Certified for 4"-40" only, 3x-FLDI is Certified for 4" - 6" only); the 70400, the 70550 and the 66213 are Controls and are part of the FLYy trims.

3x-EL: includes models 3x-EL and 3x-FLEL; with the GEM-A solenoid-valve and the 66213 relay-valve as Controls that are part of the EL and FLEL trims sizes 1.5"-40".

3x-AL: valves with the 31-10A as Controls that are part of the AL trims sizes 1.5"-6".

3x-AL-CXAL: 8"-40" valves with the CXAL as Controls that are part of the AL-CXAL trims

3x-FR with the CXSD as Controls that are part of the FR trims. 3x-FR is Certified for 8" - 40" only.

3x-PR with the 68410 and the CXPR as Controls that are part of the PR trims sizes 1.5"-40".

3x-PS with the 68510 and the CXPS as Controls that are part of the PS trims sizes 1.5"-40".

3x-QR with the 68510, 28200 and the 09AN-2-HP as Controls that are part of the QR trims sizes 1.5"-40".

3x-BC with the GEM-A solenoid-valve and the 66213 relay-valve as Controls that are part of the BC trims sizes 6"-40".

The following accessories are approved for use with the above valve models: 68410, CXPR, 68510, CXPS, CXAL and 31-10A pilot-valves, 28200 and 66213 relay-valves, 70400 and 70550 float-actuated pilot-valves, self-flushing inline filter assembly, 1/2" "Y" pattern filter assembly, isolation ball-valve, check-valve, and pipe and fittings.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

---

Number of matching Manufacturers is 1

Number of matching Products is 6

Processing time was 0 seconds